

SERVICE DOOR SP130 - CONFIGURATOR













Please complete this document and tick the corresponding boxes:

Compagny name :

Project :

☐ Quotation

☐ Order

Leaf color (snow white, ocean blue, poppy red, slate black, pearl grey, graphite grey, emerald green, lime green or mimosa yellow) : ☐ Snow white (Standard) ☐ Other :		Number of identical doors : Number of leaf(ves) : ☐ 1L ☐ 2L																		
DIMENSIONS																				
☐ OPENING DIMENSIONS  Wall Opening Width : WOW Wall Opening Height : WOH (in mm) WOH = WOW = When two leaves : ☐ Equal ☐ Unequal : W* *Main leaf clear opening width		Clear Opening Width : COW Clear Opening Height : COH <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th colspan="3">Frame / Fastening</th> </tr> <tr> <th colspan="3">(in mm)</th> </tr> <tr> <th>U, C, L</th> <th colspan="2">T</th> </tr> <tr> <td>COW</td> <td>WOW-60</td> <td>WOW-90</td> </tr> <tr> <td rowspan="3">COH</td> <td rowspan="3">COH-30</td> <td>WOH-45</td> </tr> <tr> <td>WOH-55 (When Door closer)</td> </tr> <tr> <td>WOH-55 (When cremone bolt on hinges side)</td> </tr> </table>		Frame / Fastening			(in mm)			U, C, L	T		COW	WOW-60	WOW-90	COH	COH-30	WOH-45	WOH-55 (When Door closer)	WOH-55 (When cremone bolt on hinges side)
Frame / Fastening																				
(in mm)																				
U, C, L	T																			
COW	WOW-60	WOW-90																		
COH	COH-30	WOH-45																		
		WOH-55 (When Door closer)																		
		WOH-55 (When cremone bolt on hinges side)																		
WALL TYPE																				
Sandwich panel, concrete, wood, ... :		Thickness : in mm																		
FRAME / FASTENING																				
☐ U  ☐ C  ☐ L  ☐ T 			Frame Fixing (for U or C frame) ☐ Through fixing ☐ Dowel fastening																	
OPENING DIRECTION																				
 ☐ Left pulling (right pushing)		 ☐ Right pulling (left pushing)																		
OPTIONS																				
Locks and Hardware ☐ Lock with cylinder ☐ Lock without cylinder ☐ Lock with V/E indicator on : ☐ hinges side ☐ opposite side of the hinges ☐ Door closer ☐ Cremone bolt (When 2 leaves) : ☐ hinges side ☐ opposite side of the hinges ☐ Panic bar (1 point)		Vision panel flush on both sides ☐ Round Ø 350 mm  ☐ Oblong 300x500 mm 																		
Bumpers / Protections ☐ Stainless steel 0,8 mm thick  ☐ Polyethylen 15 mm thick  ☐ Acrovyn Grey or White 1,5 mm thick  Height : (standard 240mm) HDPE / Acrovyn Color :																				
Comments : 																				

For any special request, please contact us.