

SEMI-INSULATED DOUBLE-SWING TRAFFIC DOOR SP900 - CONFIGURATOR

Please complete this document and tick the corresponding boxes:


Company name :

Project :






☐ Quotation




☐ Order





Leaf type Pre-lacquered steel sheet white RAL 9010 (Standard) ☐ Color :	Number of identical doors : Number of leaf(ves) : ☐ 1L ☐ 2L
---	--

DIMENSIONS																																																																																							
☐ OPENING DIMENSIONS				Clear Opening Width : COW Clear Opening Height : COH																																																																																			
 Wall Opening Width : WOW Wall Opening Height : WOH (in mm)				(in mm) <table border="1"> <thead> <tr> <th colspan="2"></th> <th colspan="8">Frame / Fastening</th> </tr> <tr> <th colspan="2"></th> <th colspan="2">U, C</th> <th colspan="2">L</th> <th colspan="2">Omega</th> <th colspan="2">Plates</th> </tr> <tr> <th colspan="2"></th> <th>1L</th> <th>2L</th> <th>1L</th> <th>2L</th> <th>1L</th> <th>2L</th> <th>1L</th> <th>2L</th> </tr> </thead> <tbody> <tr> <td rowspan="3">COW</td> <td>Delrin Hinge</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> </tr> <tr> <td>PE Stainless steel Hinge</td> <td>- 80</td> <td>- 150</td> <td>- 113</td> <td>- 183</td> <td>- 86</td> <td>- 172</td> <td>- 78</td> <td>- 156</td> </tr> <tr> <td>Stainless steel Hinge</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> <td>WOW</td> </tr> <tr> <td></td> <td></td> <td>- 118</td> <td>- 200</td> <td>- 151</td> <td>- 233</td> <td>- 109</td> <td>- 190</td> <td colspan="2">Incompatible</td> </tr> <tr> <td>COH</td> <td></td> <td colspan="2">WOH-5</td> <td colspan="2">WOH-22</td> <td colspan="2">WOH</td> <td colspan="2">WOH</td> </tr> </tbody> </table>								Frame / Fastening										U, C		L		Omega		Plates				1L	2L	1L	2L	1L	2L	1L	2L	COW	Delrin Hinge	WOW	WOW	WOW	WOW	WOW	WOW	WOW	WOW	PE Stainless steel Hinge	- 80	- 150	- 113	- 183	- 86	- 172	- 78	- 156	Stainless steel Hinge	WOW	WOW	WOW	WOW	WOW	WOW	WOW	WOW			- 118	- 200	- 151	- 233	- 109	- 190	Incompatible		COH		WOH-5		WOH-22		WOH		WOH	
		Frame / Fastening																																																																																					
		U, C		L		Omega		Plates																																																																															
		1L	2L	1L	2L	1L	2L	1L	2L																																																																														
COW	Delrin Hinge	WOW	WOW	WOW	WOW	WOW	WOW	WOW	WOW																																																																														
	PE Stainless steel Hinge	- 80	- 150	- 113	- 183	- 86	- 172	- 78	- 156																																																																														
	Stainless steel Hinge	WOW	WOW	WOW	WOW	WOW	WOW	WOW	WOW																																																																														
		- 118	- 200	- 151	- 233	- 109	- 190	Incompatible																																																																															
COH		WOH-5		WOH-22		WOH		WOH																																																																															
L shaped Frame : ☐ Hinge on left jamb Front view ☐ Hinge on right jamb																																																																																							

WALL TYPE	
Sandwich panel, concrete, wood, ... :	Thickness : in mm

FRAME / FASTENING					
☐ U	☐ C	☐ L	☐ Omega	☐ Plates	Frame Fixing (for U or C frame) ☐ Through fixing ☐ Dowel fastening
					

DOUBLE ACTION HINGES		
☐ Delrin with Stainless steel mechanism  ☐ With 90° blocking system ☐ Without blocking system	☐ PE with Stainless steel mechanism  ☐ With 90° blocking system ☐ Without blocking system	☐ Complete Stainless Steel  (without blocking system)

OPTIONS				
Vision Panel ☐ Oblong Vision panel 350x550 mm stadip 33,1 	Bumpers / Protections ☐ Stainless steel 0,8 mm thick  ☐ Acrovyn Grey or White 1,5 mm thick 		Stainless steel push plates ☐ W150xH250 0,8 mm thick  ☐ W150xH300 0,8 mm thick 	
Height :(standard 240 mm)				

Comments :

For any special request, please contact us.