



Semi-insulated Double-Swing Traffic Door SP900



Leaf in pre-lacquered steel sheet



Type Porte :

SP900

Leaf with full stainless steel
hinges
Stainless steel U or C shaped
Frame




SPENLE 

F-57400 SARREBOURG
+33 (0)3 87 25 78 00
www.spenle-international.com
info@spenle-international.com



C shaped Frame
 Double drilling ($\varnothing 13$; $\varnothing 6.1$)
 for fixing with dowel
 Double drilling ($\varnothing 13$; $\varnothing 8.5$)
 for through fixing

U shaped Frame
 Drilling ($\varnothing 6.1$)
 for fixing with dowel
 Drilling ($\varnothing 11.1$)
 for through fixing



*COW : Clear Opening Width
 **COH : Clear Opening Height


Type Porte :

SP900

Leaf with full stainless steel hinges
 Stainless steel U or C shaped Frame



F-57400 SARREBOURG
 +33 (0)3 87 25 78 00
www.spenle-international.com
info@spenle-international.com



*COW : Clear Opening Width
 **COH : Clear Opening Height

Type Porte :

SP900

Leaf with full stainless steel hinges
 Stainless steel U or C shaped Frame

SPENLE 

F-57400 SARREBOURG
 +33 (0)3 87 25 78 00
www.spenle-international.com
info@spenle-international.com